# STI EXIT SIGN DAMAGE STOPPER®

### Protects a Wide Range of Exit Signs From **Vandalism and Accidental Damage**

Wherever exit signs are at risk from either intentional or accidental damage, installation of our super tough wire guard is the solution to the problem. Two sizes available to cover a wide range of exit sign models available today. Installation is simple with anchors and screws provided.

#### **Backed By a Lifetime Guarantee**

As all STI protective covers, this Stopper is backed by a lifetime quarantee against breakage in normal use. It is constructed of 9-gauge, welded steel wire, coated with a tough, corrosion resistant polyester shell. To provide even greater protection against vandalism, tamper resistant screws and a matching bit are available.



STI-9640

- Super tough construction of 9-gauge coated steel wire makes it extremely difficult to break.
- Fast and easy installation.
- Two sizes available to cover a wide range of exit
- Flexible mounting options with moveable mounting clamps.
- Simple removal for light bulb replacement.

- Tamper resistant hardware is available.
- May be painted prior to installation.
- Lifetime quarantee against breakage in normal use.
- Guard may reduce projected light values. Verify correct exit light requirements when using quard (NFPA 101).



Safety Technology International, Inc. 2306 Airport Road • Waterford, Michigan 48327-1209 Phone: 248-673-9898 • Fax: 248-673-1246 Toll Free: 800-888-4STI • E-mail: info@sti-usa.com Web: www.sti-usa.com

Safety Technology International (Europe) Ltd. Unit 49G Pipers Road • Park Farm Industrial Estate • Redditch Worcestershire • B98 OHU • England • Tel: 44 (0) 1527 520 999 Fax: 44 (0) 1527 501 999 • Freephone: 0800 085 1678 (UK only) E-mail: info@sti-europe.com • Web: www.sti-europe.com

## EXIT SIGN DAMAGE STOPPER® Dimensions and Technical Information

**STI-9640** Exit Sign Damage Stopper **STI-9740** Exit Sign Damage Stopper **SUB-82** 

Tamper resistant screws, #8 X 1 1/2 in.

snake eye (quantity 4)

19038 Tamper bit for tamper resistant screws

When lights are used for emergency exit corridor lighting, this guard can reduce projected light reading on floor. Verify field conditions as required by NFPA 101 life safety.

Model	Width	Height	Depth
STI-9640	13.75 in. (349mm)	10.5 in. (267mm)	2.75 in. (70mm)
STI-9740	20.5 in. (520mm)	15.5 in. (394mm)	6 in. (152mm)



